



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : A47B 9/10, A47C 3/30, B25H 1/16 // A47B 9/20, A47C 3/40</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/55197</p> <p>(43) International Publication Date: 4 November 1999 (04.11.99)</p>
<p>(21) International Application Number: PCT/DK98/00180</p> <p>(22) International Filing Date: 7 May 1998 (07.05.98)</p> <p>(30) Priority Data: 00142/98 15 April 1998 (15.04.98) DK</p> <p>(71) Applicant (for all designated States except US): SYSTEM B8 MØBLER A/S [DK/DK]; Martin Bachs Vej 3-5, DK-8850 Bjerringbro (DK).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): NIELSEN, Tyge, Frank [DK/DK]; Kristiansvej 6, DK-8686 Skanderborg (DK).</p> <p>(74) Agent: HARALDSTED, Hans, H.; Ing.-& Handelsfirma ApS, Ellegaardspark 19, P.O. Box 107, DK-3520 Farum (DK).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published With international search report. With amended claims. In English translation (filed in Danish).</p>
<p>(54) Title: TELESCOPIC ARRANGEMENT WITH DOUBLE STROKE</p> <p>(57) Abstract</p> <p>Telescopic arrangement (1), especially a hydraulic (14) arrangement, and especially for system of furniture, but also for other systems or arrangements (1), which shall be lifted (4.1/11, 4.2/11) or lowered (12). It contains a coupled (3) double stroke (4.1, 4.2) arrangement of cylinders (5.1, 5.2). The respective stroke of these cylinders (5.1, 5.2) is directed opposite to each other (19.1, 19.2). The opposite directed strokes could ideally move along the same line.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Telescopic arrangement with double stroke

The invention relates to a telescopic arrangement, especially hydraulic, and especially for system of
5 furnitures, but also other systems or arrangements, which shall be lifted or lowered.

Hitherto have one by the system of elevating especially used of the branch of furnitures, where one
10 especially have to had strokes as an example over 35 cm, with an elevating of weight as an example from 100 kg and over that, used solutions of mechanical screw-spindles.

The disadvantage by this system is that it is very
15 expensive, complicated and complexed to use.

Hitherto have one also establish elevating systems via hydraulic. Where one then have had one cylinder there in its self has the whole stroke.

20 One of the disadvantage has here been that the lower minimum high has been limited, as the piston rod fully extended necessary also must have an extra length of guiding/holding.

In the same time has the arrangement of pump for an
25 synchron elevating or lifting, especially if it has been made as a pump-unit of magazine cylinders, been impossible to made compact both according to the thickness as according to the stroke. As then the pump unit on a furniture, almost will be impossible to
30 place, because of now its outer extra necessary larger size.

The system will moreover also here be expensive to established.

35 The purpose with the invention is, to provide an arrangement for lifting or lowering of this in beginning mentioned sort or kind, where one obtain a

relative long stroke, with a relative large stationary as dynamic activated lift, establish of/by one in itself compact embodiment or arrangement of elevating.

5

The new of the invention is that the telescopic arrangement 1 especially can contain of a coupled 3 double stroke 4.1 and 4.2 arrangement of cylinders 2. Where the one 5.1 of the compact cylinder arrangements 2 is turning opposite the other, and with a diametrically opposite directed stroke 4.1 as 4.2. And where the "stroke" 4.1 or 4.2 according to the direction of movement or the direction of operation 4.1 as 4.2 ideal for that matter generally has a line
10
15 convergence.

With the new telescopic arrangement 1 according to the invention one can obtain that one compact and very easy can establish one in itself generally self
20 guided and leaded unit 2 out of area of the elevating. Generally with standard components as an example hydraulic cylinders 5.1 as 5.2. And where one by a building together 3 according the invention extend the area of function of thies standard components 5.1 and
25 5.2 to a double lenght of stroke 11 with generally the same possibility of loading or limit, as for one cylinder 5.1 or 5.2.

The telescopic arrangement 1 will especially be
30 driven optimal, where one as an example use hydraulic. And where the system of pump 6 as an example is of the type magazine cylindres 7, which is couble toghter "as bundles" 8 and 9. And for that matter ideal has been force guided synchronic 18 in the
35 stroke. As an example 2 cylinders 5.1 and 5.2 here in the same time 3 will be able to be driven or lifte

4.1 as lower 4.2 as an example a telescopic leg 10 or a like unit 10.

The invention shall after this be explain neare in
5 the following according to the drawing, where

Fig.1 shows, seen in a generally perspective a lifting/lowering system 5.1 and 5.2, where an arrangements of the hydraulic cylinder 5.1 as 5.2 is
10 established respectively as telescopic leg 10. And where a pumping system 6 for that matter also a shown. As the telescopic arrangement 1 or elevating unit 1 here is made as 2 opposite pointing cylinders 5.1 as 5.2. Which in the telescopic arrangement 1 are
15 coubled 3 "floating" together by the houses of the cylinders 5.1 and 5.2.

The stroke 4.1 and 4.2 of the arrangement 1 can be seen indirect as a "maximum-stroke" 11, as opposite
20 as a "minimum-stroke" 12. As it clearly can be seen that the minimal high 12 "only" almost is limited of the high of the cylinder house 5.1 as 5.2. And if the 2 opposite pointing pressure cylindres 5.1 as 5.2 are builed together 3 in the same niveau or plan as shown
25 on Fig.1, then will this establish an extrem low high of build 11.

An optimum example on a pumping arrangement 6 according to the invention is also shown in Fig. 1. As
30 there here are shown a magazine system 7 containing of coubled and mutual forced guided 18 pumping cylinders 7.

For the shown arrangement 2 is used 2 cylinders, here
35 indicated by its no. 5.1 as 5.2. As a forward conveying 8 as a backward conveying 9 in the house of

the pump 6 respectively will course an synchron lifting 4.1/4.2 or 11 as lowering 17. Especially if the dimension of the cylinders in the pump 6 as at the telescopic arrangement 1 generally are the same.

5 An ideal guiding or leading of the pipe-line 13 of the oil pressure pipe line 19 from/to each cylinder 5.1 as 5.2, will also ideal be able to be establish only as one pipe line 13 to/from each cylinder 5.1 as 5.2.

10

The pipe line 14 to/from lifting/lowering arrangement 1 to/from the pump arrangement 6 can be solid mounted or fixed to the telescopic arrangement 1. While thies 13 inside in the telescopic-arrangement 1, as the present embodiment shows, shall be made or mounted as flexieble and loose movable.

On the pumping arrangement itself 6 in Fig.1 is shown an example on an activating arrangement 15. 16 and 20 18, here as a revolving handle 15. Where one then manual here shall turn 16 to activat the telescopic unit for lifting 4.1/4.2 as for lowering.

The system 1, 2 and 6 could also be establish motor 25 driven.

Fig.2 shows an activated and moved telescopic arrangement 1, with a shown embodiment with an ideal placing of the comming supplying lines or pipes 14 in 30 the top of the arrangement. And where the arrangement 1 for that matter is shown at its or under the maximum lenght of a stroke 11.

Fig.3 shows a compressed telescopic arrangement 1, 35 in its minimal high of stroke 12.

The house of the telescope 1, contain of here as an

example of 3 coubled and sliding shells or cases 17.
Ideal made of aluminium, steel, plast or like. And
where the cases 17 mutual are guided as an example
via a covering of plast or like material of bearings.

CLAIMS

1. Telescopic arrangement (1), especially hydraulic (14), and especially for system of furnitures, but also other systems or arrangements (1), which shall be lifted (4.1/11 as 4.2/11) or lowered (12), characteristic of, that it contains of a coupled (3) of a double stroken (4.1 as 4.2) arrangement of cylinders (5.1 as 5.2), where the one arrangement of cylinders (5.1 or 5.2) turn opposite the other, and with an opposite pointing stroke, and where the opposite turned strokes (4.1 or 4.2) in the direction of movement or the direction of the operation (19.1 as 19.2) ideal can have a line covering or a line convergence.

2. Telescopic arrangement (1) according to claim 1, characteristic of, that a joint coupled (3) arrangement of cylinders (5.1 and 5.2) is floating fixed (3) to or by each other diametrically opposite directed houses of cylinders (5.1 as 5.2).

3. Telescopic arrangement (1) according to claim 1, characteristic of, that an arrangement of lifting cylinders (5.1 and 5.2) ideal can be covered of one in itself guided, but following and in it self displacing telescopic mantle or housing or like arrangement (17).

4. Telescopic arrangement (1) according to claim 1, characteristic of, that the telescopic arrangement (1) or like (1) in its top (20) as its bottom (21), ideal can have an arrangement of mounting -or fixing for the diametrically opposite turned end of application of the cylinder

rods (19.1 and 19.2) or the end of the piston rods itself (19,1 as 19.2) or like.

5. Telescopic arrrrangement (1) according to
5 claim 1, c h a r a c t e r i s t i c o f, that
lines or pipes (13) for the activating of the arran-
gement of lifting/lowering (4.1 as 4.2) ideal can be
mounted among here fixed and leaded in from the top
(20) as an alternative from the bottom (21) of
10 telescopic arrangement (1) or like (1), and that
thies or the pipes or lines (13) into the cap of the
telescop or like arrangement (17) under the opera-
tions (4.1 as 4.2) generally are flexieble and
movable.

15

6. Telescopic arrrrangement (1) according to
claim 1, c h a r a c t e r i s t i c o f, that
where the means of power or energy is of hydraulic
kind (22), that there can each unit (5.1 as 5.2) of
20 an arrangement of a double strok cylinders(5.1/5.2)
ideal in the same time be synchronic activated (18/15-
/16), respectively be driven forward (4.1/4.2) as be
lowered (12) via an arrangement of pump (6), espe-
cially containing of more side by side in or as
25 laying magazines, synchronic and moved (8 as 9) in the
same direction, as activated (16) and hydraulic
cylinders (7) fixed together, especially ideal of the
same size and dimension, and with an activating
cylinder (7) for each dirementrally opposite turned
30 cylinder of telescop (5.1 as 5.2), and where thies
activating cylinders (7) for that matter ideal can be
forced guided together.

7. Telescopic arrrrangement (1) according to
35 claim 1, c h a r a c t e r i s t i c o f, that a
mutually movable or displacable house of telescop

(17) or like arrangement (17) for units of lifting/-
lowering (11/12) ideal can be guided or leaded in its
or they mutual parts via a padding or with covering
means or parts of material of bearings as an example
5 as plastic, metal or like.

AMENDED CLAIMS

[received by the International Bureau on 8 July 1999 (08.07.99);
original claims 1-7 replaced by new claims 1-4 (2 pages)]

1. Method for integrated "ad hoc" stop arrangement
(8 and 9) on especially telescopic elevating arrangement (1) with especially coupled (3) and driving
5 together as opposit turning hydraulic elevating (4.1
and 4.2) cylinders (5.1 and 5.2), c h a r a c t e -
r i s t i c o f, that stop as "ad hoc" locking arrangement
for the driving together cylinders (5.1 and
10 5.2) has been establish and integrated qua an arrangement
of postion guided pumps (6).

2. Stop arrangement (8 and 9) for telescopic
elevating arrangement (1) with opposit turned and
15 simultaneous cylinder units (5.1 and 5.2) according
to claim 8, c h a r a c t e r i s t i c o f, that
the opposite turned as simultaneous cylinders (5.1
and 5.2) in a telescopic cylinder unit (1), ideal as
an example can be activated for an exact mutual
20 synchronous movement ahead, as return, as stop by a
pump battery (6) with screw/nut-guiding or activating
or like, and especially ideal with parallel mutual
laying pump cylinders (7) for each cylinder unit (5.1
as 5.2) on/in the single unit of telescopic arrangement
25 (1) or generally in an arrangement with two
cylinder (5.1 and 5.2) for each telescopic unit (1).

3. Stop arrangement (8 and 9) for telescopic
elevating arrangement (1) with opposit turned and
30 simultaneous cylinder units (5.1 and 5.2) according
to claim 8 as 9, c h a r a c t e r i s t i c o f,
that the pump arrangement (6) for the telescopic unit
of cylinder (1) can consist of a worm/screw guided
arrangement of pump-cylinder (7), where a guided
35 straight lined force (8 as 9) of this can be made
indirect via a sledge/ pal guided yoke for each

arrangement of pump (6) of the telescopic unit (1).

4. Telescopic arrangement (1) with belonging accessories according to claim 1, c h a r a c -
5 t e r i s t i c of, that lines or pipes (13) for the activating of the arrangement of lifting/loving and stopping (4.1 as 4.2) ideal can be mounted among here fixed and leaded in from the top (20) as an alternative from the bottom (21) of thelescopic
10 arrangement (1) or like (1), and that thies or the pipes or lines (13) into the cap of the telescop or like arrangement (17) under the operations (4.1 as 4.2) generally are flexieble and movable.

Fig.1




Fig.2





Fig.3



INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 98/00180

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A47B 9/10, A47C 3/30, B25H 1/16 // A47B 9/20, A47C 3/40
 According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A47B, A47C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR 2691889 A1 (SOCIETE JEANNEAU - CONSTRUCTIONS NAUTIQUES SOCIETE ANONYME), 10 December 1993 (10.12.93) --	1-7
A	SE 449044 B (ERIK HALLBERG), 6 April 1987 (06.04.87) --	1
A	US 5322025 A (SHERMAN ET AL), 21 June 1994 (21.06.94) --	1
A	US 5553550 A (DOYLE), 10 Sept 1996 (10.09.96) -- -----	1



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance
 "E" earlier document but published on or after the international filing date
 "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
 "O" document referring to an oral disclosure, use, exhibition or other means
 "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 February 1999

Date of mailing of the international search report

14 -02- 1999

Name and mailing address of the ISA/
 Swedish Patent Office
 Box 5055, S-102 42 STOCKHOLM
 Facsimile No. +46 8 666 02 86

Authorized officer

Lena Nilsson
 Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

21/12/98

International application No.
PCT/DK 98/00180

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR 2691889 A1	10/12/93	NONE	
SE 449044 B	06/04/87	SE 8402001 A	12/10/85
US 5322025 A	21/06/94	NONE	
US 5553550 A	10/09/96	CA 2145265 A	01/10/95